This Business System has been produced by RAAS (UK) Ltd and must not be used in whole or in part without the express prior permission of © RAAS (UK) Ltd 2010

ADSHAW WILLIAM

ANNUAL EXCAVATOR SLI CHECK SHEET

MAKE/MODEL: CASE 988	988	DATE OF INSPECTION:	NEXT INSPECTION:	
ENGINEER: B. FELL		SIGNATURE:	XV	FLEET NO: 12
	Displayed Radius	Measured Radius	Known Weight Screen Weight	ASLI Function Pass/Fail
Max. Radius	Wbo t	7.121		PASS
MID. RADIUS	SSIM	5.487		PASS
Min. Radius	4.28M	4.240		PASS
LARGE WEIGHT			1940KG 1970KG	PASS
SMALL WEIGHT		/	1180KG 1150KG	PASS
SLEW LIMIT	LEFT:	MOTION CUT:	RIGHT:	MOTION CUT:
Неіднт Lіміт	Boom:	Dipper:	ARTIC BOOM:	MOTION CUT:
DATA LOGGER DOWNLOADED	YES (TICK)		DATA LOGGER RECORDING OK	YES (TICK)

METHOD:

- Set at maximum radius of machine taken from the duty charts and then tape from the centre of the slew ring to the centre of the lifting hook
- Record both the displayed radius and the actual taped measurement.
- Repeat for the minimum chart radius plus a mid-point check and record as above. If radius checks okay, proceed with steps 5 8. IF NOT DO NOT PROCEED but arrange corrective action.
- Lift a known weight at the max. radius detailed in the charts for that weight
- Repeat this using a small known weight.
- Check the results are within the calibration as specified by PROLEC.
- Check slew left and right for operation of limitation and motion cuts in both directions
- 10 98 7 6 5 4 3 2 7 Check excavator arm height limitation and motion cuts against machine acceptance certificate.
- REPORT ANY FINDINGS WHICH REQUIRE FURTHER CLARIFICATION OR ATTENTION

Document Ref:	No of Pages:	Issue Date:	Issue No:
WBP-LAFT 01	Page 1 of 1	Oct 2016	4.1