



ENGINEERING ACCEPTANCE CERTIFICATE

This certificate issued in accordance with RIS-1530-PLT Issue 5.

NAME OF CERTIFICATION BODY

Atkins Rail

ACCREDITATION CODE

NS

Vehicle Class/Description Road-Rail Vehicle – Philmor Rail Trailer T5020HAS (Type OA)

Vehicle Owner William Bradshaw Plant Hire

Issue Date 8th May 2015

Expiry Date 8th May 2022

Vehicle Serial Number: 99709 010048-5

FIRST OF CLASS

Certificate number of First of Class

YES	NO
	X

Not known/not provided.

Authorised by :

Signatory Name:

SP Rice

Authorised Signatory:

Reason for issue and Scope of Work

Previous scope of work;

Certification of new rail trailer.

Assessed for compliance with RIS 1530-PLT Iss 1. Philmor build specification E2755.

Network Rail ID and machine serial numbers: 99709 010048-5 (2313)

Network Rail Deviation (lighting, clause 5.13.1.6.) NR/07/1530/039/ DGN applies to this certificate.

Expiry date conforms to the requirements of RIS-1530-PLT.

Scope of work for this certificate;

Upgrade to RIS-1530-PLT, Issue 5. June 2014.

Installation of air park and service brake system.

Removal of Derogation NR/07/1530/039, this no longer applies.

New maintenance plan.



Deviations associated with this certificate: None

Previous Engineering Acceptance certificate number: IF/0184/08

Previous Maintenance certificate: IF/MP/0103/08

Maintenance plan Id.	Identification Number	Issue No.	Date
Maintenance plan title	APM039	1	05-15
	APPL – Philmor Rail Trailer (Upgrade) Operation and Maintenance Manual		

Limitations of Use

1. In travelling and working modes, the trailer is within W6a gauge as defined by RIS-1530-PLT.
2. Trailers shall only operate inside possessions.
3. It has hydraulic/air spring-operated emergency /park brake and hydraulic/air operated service brake:
 - Hydraulic park brake release pressure 30-180bar; service brake pressure 0-100bar.
 - Air park brake release pressure 4-8bar; service brake pressure 0-8bar.
4. Trailers may only on or off track, travel and work under live OLE in accordance with Method Statement for the possession as determined and authorised in accordance with the requirements of GE/RT8024.
5. Trailers shall **NOT** on or off track or work on live conductor rail lines.
6. Trailers may not activate train operated points.
7. Trailers shall only be coupled to RRV's or RMMM's which are certificated for towing or propelling this type of trailer.
8. Trailers shall be subject to limitations of the towing vehicle.
9. Trailer **cannot** be on/off tracked in laden condition.
10. For on/off tracking, a site specific plan shall be used taking account of the applicable module of Network Rail Infrastructure Plant Manual NR/PLANT/0200.

Maximum speed of vehicle in travelling/working mode;	10mph.
Maximum speed of vehicle in travelling/working mode over switch & crossings;	5 mph.
Maximum permitted speed through raised check rails;	1 mph.
Maximum track cant;	200mm.
Maximum gradient;	1:25.
Maximum gradient on which vehicle can be on/off tracked;	1:25.
Maximum cant on which vehicle can be on/off tracked;	100mm
Minimum Radius;	80m.

Supplementary Information

1. Vehicle Numbers: Serial No. 2313. Fleet No. FN59.
2. Vehicle is a Philmor 4 wheel rail trailer with 5m bed to work with compatible RRV.
3. System for vehicle recovery and on/off tracking:
 - As detailed in APM039, see Limitations of use 9 & 10.
4. Applicable Braking Curve; RIS-1530-PLT Clause 5.6.2.
5. Capacity;
 - Tare weight 2.9t tonnes
 - Maximum payload 20 tonnes, evenly distributed, shall not be exceeded.